Adjustments

\land Warning!

Before riding, always make sure that the basic settings made by Öhlins are according to recommended Set-up Data. Read about adjustments and setting up in the Öhlins Owner's Manual before you make any adjustments. Contact an Öhlins dealer if you have any questions about setting up the shock absorber.

Set-up Data

Recommended set-up

Rebound Spring Preload

Spring

Part No. 01091-29 Free Spring length Shock absorber data Length Stroke

Spring Preload

Adjuster

Rebound

14 clicks

11 mm

Rate

90 N/mm

160 mm

Damping Adjuster


Set-up Recommendations F1-F2 = 25 mm (Öhlins Front fork springs) F1-F3 = 35 mm R1-R2 = 11 mm R1-R3 = 37 mm

0

Ohlins products are subject to continuous improvement and development, therefore, although these instructions include the most up-to-date information available at the time of printing, minor updates may occur.

To find the latest information contact your Öhlins distributor. Please consult your Öhlins dealer if you have any questions regarding the contents in this document.

> Part no. SU905_0 Issued 2009-04-08



Öhlins Racing AB Box 722 S-194 27 Upplands Väsby, Sweden Phone +46 8 590 025 00 fax +46 8 590 025 80



317 mm

65.5

www.ohlins.com

Before installing this product, check the contents of the kit. If anything is missing, please contact an Öhlins dealer.

Kit Contents

t No.	Pcs.
905	1
10-02	1
92-01	2
80-01	1
41-02	1
	905 '10-02 92-01 80-01

Please note that during storage and transportation, especially at high ambient temperature, some of the oil and grease used for assembling may leak and stain the packaging. This is in no way detrimental to the product, wipe off the excessive oil/grease with a cloth.

\land Warning!

Before installing this product, read the Öhlins Owner's Manual. The shock absorber is an important part of your vehicle and will affect the stability.

Shock Absorber for Suzuki SFV 650 Gladius **SU 905**

Mounting Instructions



How to install

Warning!

It is advisable to have an Öhlins dealer install the shock absorber.


When installing, consult your Vehicle Service Manual.

1

Put the motorcycle on a workstand so that the rear wheel barely touches the ground.

Warning!


Make sure the vehicle is securely supported so that it will not tip.



Remove the seat.


3

Remove the left side cover.



4

Remove the screw indicated on the figure to reach the lower attachment of the original shock absorber.



Remove the upper attachment of the original shock absorber and remove it (by lifting it towards the rear).

Note!

5

Before installing the Öhlins shock absorber clean the vehicle thoroughly.

6

Install the Öhlins shock absorber in the same way as the original unit.

Note!

Lower the motorcycle so that the shock absorber is slightly compressed, before tightening the screws.

7

Tighten the upper and the lower attachments. Make sure that all removed parts are reinstalled in the same way as they were before the installation of the Öhlins shock absorber.

"Caution!

Make sure that all screws are tightened to the correct torque and that nothing fouls or restricts movement of the shock absorber when the suspension is fully compressed or extended.

