


Adjustments

⚠ Warning!

Before riding, always make sure that the basic settings made by Öhlins are according to recommended Set-up Data. Read about adjustments and setting up in the Öhlins Owner's Manual before you make any adjustments. Contact an Öhlins dealer if you have any questions about setting up the shock absorber.



Recommended set-up

Spring Preload 10 mm
Rebound click 18

Total length 345 mm
Stroke 83 mm
Spring free length 190 mm
Spring rate 80N/mm

Recommended Sag and Ride Height

F1 - F2: 40-50 mm
F1 - F3: 55-65 mm

R1 - R2: 15-25 mm
R1 - R3: 40-50 mm

👁 Read more about sag and ride height in the Öhlins Owner's Manual.

Before installing this product, check the contents of the kit. If anything is missing, please contact your nearest Öhlins dealer.

Kit Contents

	Part No.	Pcs.
Shock abs S46DR1	YA 054	1
C-spanner single	00710-02	1
Öhlins Sticker	00192-01	2
Memo Notes Sticker	01180-01	1
Owner's Manual	07241-02	1

Please note that during storage and transportation, especially at high ambient temperature, some of the oil and grease used for assembling may leak and stain the packaging. This is in no way detrimental to the product, wipe off the excessive oil/grease with a cloth.

⚠ Warning!

Before installing this product, read the Öhlins Owner's Manual. The shock absorber is an important part of your vehicle and may affect the stability of your vehicle.

👁 Öhlins products are subject to continuous improvement and development, therefore, although these instructions include the most up-to-date information available at the time of printing, minor updates may occur.

To find the latest information contact your Öhlins distributor. Please consult your Öhlins dealer if you have any questions regarding the contents in this document.

Part no. YA054_0
Issued 2010-12-03



© Öhlins Racing AB. All rights reserved. Any reprinting or unauthorized use without the written permission of Öhlins Racing AB is prohibited.

Öhlins Racing AB
Box 722
S-194 27 Upplands Väsby, Sweden
Phone +46 8 590 025 00
fax +46 8 590 025 80



www.ohlins.com

Shock Absorber for Yamaha XT660Z Tenere YA 054

Mounting Instructions



⚠ Warning!

It is advisable to have an Öhlins dealer install the shock absorber.

When installing, consult your Vehicle Service Manual.

1

Put the motorcycle on a workstand so that the rear wheel barely touches the ground.

⚠ Warning!

Make sure the vehicle is securely supported so that it will not tip.

👉 Caution!

Use masking tape to protect painted parts from scratches when working on the motorcycle.

2

Remove the seat.

3

Remove the exhaust heat protectors on the left side.

4

Remove the passenger handles and the cover behind them.

5

Remove the rear mud guard.

6

Remove the heat protectors from the silencers.

7

Remove the silencers and exhaust pipe, to gain access to the upper bracket.

8

Loosen the rubber mud guard at the swing arm.

9

Remove the lower and upper shock attachment bolts. Remove the original shock absorber from the rear.

👁 Note!

Before installing the Öhlins shock absorber clean the vehicle thoroughly.

10

Install the Öhlins shock absorber. Do not tighten the shock mounting bolts yet.

👁 Note!

Lower the motorcycle so that the shock absorber is slightly compressed, before tightening the screws.

11

Tighten the shock mounting bolts to the correct torque according to Yamaha spec.

12

Reinstall all parts in reverse order. Make sure that all removed parts are reinstalled in the same way as they were before the installation of the Öhlins Shock Absorber.

👉 Caution!

Make sure that all screws are tightened to the correct torque and that nothing fouls or restricts movement of the shock absorber when the suspension is fully compressed or extended.

